



Rewinder



Italian Leader Worldwide
EUROMAC
SLITTERS REWINDERS

Euromac Costruzioni Meccaniche S.r.l. - Strada Statale 31 n.6 - 15030 Villanova Monf. - Italia
TEL. +39 0142.483195 - FAX +39 0142.483611 - www.euromacslitters.com • euromac@euromacslitters.com



RB-3 Rewinder

UNWIND - Separate Shaftless or shafted unwinder • Dancing roller for tension control • Pneumatic Brake or electric Motor

- Automatic webguiding system.

SLITTING - Edge trim Slitting system with oscillating Razorblades and/or Shear cut rotary blades • Specific web path for Wrap-cut or Tangent-cut.

WEB PATH - Compact, Footboard or Overhead web path • Aluminum idler rollers • Driven main pull roll with own pressure roller or "S" wrap.

REWIND - Centre drive rewind with lay-on roll • Air expanding rewind shaft or shaftless • Independent lay-on roller with pneumatic pressure control • Tension regulation by multiple systems • Roll offloading by trolley.

AUTOMATION - PLC for all machine functions and controls • Touch screen digital operator panel • Modem for remote monitoring.



MAIN SPECIFICATION	Standard	Option
Maximum web widths	1.000 to 2.200 mm	(or Custom)
Maximum rewind diameter	600 to 1.200 mm	(or Custom)
Maximum unwind diameter	600 to 1.200 mm	(or Custom)
Webguide stroke	+/- 75 mm	(or Custom)
Core diameter	76, 152 mm	(or Custom)
Maximum working speed	400-800 m/min	(or Custom)
Web tension range	Customised	
Rewind system	Centre and Lay-on rolls	(Gap rewind)
Slitting	Oscillating razors	(Shear)
Material	Monolayers (CPP, BOPP, BOPA, BOPP, PVC, PET), Laminates, Coextrusion films, Paper, Paper/PE, Metalised films. Aluminum foil.	